



### MISURE STANDARD STANDARD MEASURES

	300 x 200	300 x 300	300 x 400	300 x 500	400 x 200	400 x 300	400 x 400	400 x 500	500 x 200	500 x 300	500 x 400	500 x 500
A	300	300	300	300	400	400	400	400	500	500	500	500
B	200	300	400	500	200	300	400	500	200	300	400	500
La	195	195	195	195	295	295	295	295	395	395	395	395
Lb	182	282	382	482	182	282	382	482	182	282	382	482
Amin	174	174	174	174	274	274	274	274	374	374	374	374
Bmin	161	261	361	461	161	261	361	461	161	261	361	461
T	9	9	9	9	9	9	9	9	9	9	9	9
H	255	255	255	255	255	255	255	255	255	255	255	255
Ht	243	243	243	243	243	243	243	243	243	243	243	243
Hc	252	252	252	252	252	252	252	252	252	252	252	252

### INFORMAZIONI TECNICHE TECHNICAL INFORMATION

- sezione pilastro Ø 89 mm sp 3 mm
- sezione trave Ø 89 mm sp 3 mm
- dimensione massima 500x500 cm
- profili in acciaio inox satinato
- tetto microforato ombreggiante

- pillar section Ø 89 mm sp 3 mm
- beam section Ø 89 mm sp 3 mm
- maximum size 500x500 cm
- brushed stainless steel profiles
- microperforated and shading roof

### OPZIONI COLORE COLOUR OPTION

#### Struttura Structure:

Colore standard *standard colour*

acciaio inox satinato *brushed stainless steel*

#### Telo di copertura Awning colors:

Tessuto standard *standard fabrics*

#### TENT MESH

759 natural

704 desert sand